

NON-DETERGENT MOTOR OIL

LIGHT DUTY CRANKCASE OIL FOR OLDER CARS - SB/CA

Product Description: NON-DETERGENT MOTOR OIL is manufactured from selected high viscosity index paraffin base oils which contain effective oxidation, corrosion, mild antiwear, and foam inhibitors.

Features:

- High viscosity index.
- Mild antiwear protection.
- Economical

Typical Uses:

- Meets or exceeds API Service Classification SB/CA
- Recommended for pre 1964 cars or vehicles with high oil consumption.
- Used in gear cases, manual transmission, and hydraulic systems where non-detergent oil is recommended.
- Used as a "deep well" pump lubricant.
- Also commonly used as chain and general machine shop lubricant.

Typical Specifications:

Grades, SAE	10W	30	40	50
Gravity °API	30.9	28.5	27.6	26.3
Flash Point, °F.	420	450	460	470
Fire Point, °F.	440	480	515	525
Pour Point, °F.	-10	0	5	15
Viscosity:				
SUS @ 100° F.	182	588	810	1343
SUS @ 210° F.	45.0	67.7	78.3	102.3
cSt. @ 40° C.	35.3	112.4	153.8	253
cSt.@100° C.	5.69	12.0	14.6	20.2
Viscosity Index	99	95	93	92
Color, D-1500	2.0	5.0	7.0	7.5
Sulfated Ash, Wt.%	0.2	0.2	0.2	0.2
Zinc, Wt.%	0.060	0.060	0.060	0.060

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY