

SMOKELESS TWO-CYCLE MOTOR OIL

AIR-COOLED TWO-CYCLE OIL (50:1 DILUTION)

Product Description: SMOKELESS TWO-CYCLE MOTOR OIL (AIR COOLED) is manufactured from premium quality base oil designed to minimize carbon deposits and fortified with low ash additive which provides high temperature protection to air cooled engines. Low ash formulation is designed to minimize spark plug fouling and combustion chamber deposits.

Features:

- Pre-mixed for easy use.
- Special "oiliness" additives to prevent piston and cylinder scuffing.
- Excellent high temperature engine protection.
- Suitable for engines requiring SAE 30 or 40 oil (pre-diluted).
- Low ash formulation prevents plug fouling, port plugging, and ring sticking.
- Excellent rust protection.
- Extra clean performance.
- JASO FC certified.

Typical Uses:

- Air cooled two-cycle engines.
- Water cooled two-cycle engines where NMMA Certified Lubricant For Service TC-W is not required.
- Two-cycle engines on lawn mowers, motor scooters, chain saws, portable generators, mopeds, motorcycles, and snow blowers.
- Meets JASO FB and FC requirements.
- NOT recommended for four-cycle lawn mowers or other small four-cycle engines where oil is added to crankcase.

NOT RECOMMENDED FOR FOUR-CYCLE LAWN MOWERS OR OTHER SMALL FOUR-CYCLE ENGINES WHERE OIL IS ADDED TO CRANKCASE.

Typical Specifications:

Grades, SAE	Results
Gravity °API	33.8
Flash Point, °F.	200
Pour Point, °F.	-15
Viscosity:	
SUS @ 100° F.	256
SUS @ 210° F.	54.8
Viscosity Index	146
Color	Blue

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY